






ALARM ACCESSORIES


<i>HO-103</i>	<i>PIEZO SIREN</i>
	ABS Housing in Blue or Red Rated Current (mA): 300 Rated Voltage (VDC): 12 SPL (dB):110 + 3 Gross Weight (g): 145 Measurement (mm): 122.2x72.8x43


<i>HC-06-1200</i>	<i>HIGH POWER SIREN</i>
	ABS Housing in Black Rated Current (mA): 1200 Rated Voltage (VDC): 12 SPL (dB): 115±3 Gross Weight (g): 406 Measurement (mm): Ø90x120.2x110


<i>AS 1089</i>	<i>INTERNAL SIREN</i>
	ABS Housing in White Rated Current (mA): 800 Rated Voltage (VDC): 12 SPL (dB):108 + 3 Gross Weight (g): 475 Measurement (mm): 110x110x55.4

<i>TS-TS</i>	<i>TAMPER SWITCH</i>
	N.C. Contact when depressed Protects Alarm Control Panel Box or siren Box Easy Mounting Bracket No Tool is Required Measurement (mm): 73(H)xØ19xØ24

<i>HO-02</i>	<i>PANIC BUTTON</i>
	ABS Plastic Contact Mode: COM. / N/O Rated Current (mA): 300 Rated Voltage (VDC): 250 Gross Weight (g): 21.25 Measurement (mm): 76x14x14

<i>HC-805</i>	<i>EXTERNAL SIREN</i>
	Weather resistant polycarbonate housing Rated Current (mA): 280 Rated Voltage (VDC): 9 Xenon flash 60 time/min Gross Weight (kg): 1.2 Measurement (mm): 295x190x70

<i>HO-01</i>	<i>Panic Button w/ Key Reset</i>
	ABS Plastic Contact Mode: COM. / N/O Rated Current (mA): 300 Rated Voltage (VDC): 250 Gross Weight (g): 45 Measurement (mm): 53.6x53.6x27.3

<i>TS-SSL</i>	<i>Small Strobe Light</i>
	Installation: Two (2) Screws Rated Current (mA): 120 Rated Voltage (VDC): 12 90 Flashes/Min Gross Weight (g): 138 Measurement (mm): Ø70x45