




## Multiple type Home Videophone



### Diagram



## [ KVM-520 ]

- 4" CRT B/W VDP
- For single house & multi apartment, condominium & villa system (upto 450 houses) are available
- Up to 5 indoor units (4 monitor & 1 audio handset, KIP-603) and 1 front door camera connection
- Internal call & conversation function between extended indoor units in a house
- Audio + video conversation with visitor
- Audio open (front door & common gate) function
- Call & conversation function with guard master
- Upto 3pcs of common gate cameras connection in a building

### Specifications

Model no.	KVM-520	
Power	Trans AC220V $\pm$ 10% or AC 110V $\pm$ 10%	
Power consumption	Max. 15W, Stand by 1W	
Assurance temperature	0°C ~ +50°C	
Communication systems	Duplex handset conversation	
CRT	4" flat tube	
Wiring	4wires (front door camera), 6wires (common gate camera)	
Max. wiring distance	Ø0.65 single cable : 50m, 5C-2V coaxial cable : 100m (front door camera)	
Mount type	Surface mount	
Dimension (mm)	210(W) x 222(H) x 57(D)	
Weight (approx. kg)	1.7kgs	
Camera connection	Front door camera	KC-B61, KC-B63, KC-D20
	Common gate camera	KLP-100, KLP-104, KLP-108, KLP-112 KLP-P100, KLP-P104, KLP-P108, KLP-P112

• The product may include option or additional functions.

### [ Multi-entry Type Configuration ]

